



Price information

Electric four wheel counterbalance forklift truck

CBH 2.5-3.0

Changes and errors excepted.

The prices are non-binding and apply on the basis of our framework agreement or our general terms of delivery.

anton
BY JUNGHEINRICH

Basic truck

Basic truck	CBH 2.5 (V1: ZT3300, ISS, ZH1)	CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1)	CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3)
Part number	52536539	52536540	52536542
Load capacity/load	2500 kg		
total width	1154 mm		
Turning radius	2300 mm		
Throughput	150 t/h		
Load centre distance	500 mm		
Fork dimensions	40 x 122 x 1150 mm		
Tyres	Super-elastic (SE)		
Tyre size, front	7.00-12		
Tyre size, rear	18x7-8		
Fork carriage connection class	2A		
Type of drive control	AC		
Drive motor, performance S2 60 min	17 kW		
Operation	Seat		
Lift motor, performance with S3	26 kW		
Energy consumption according to EN cycle	7.1 kWh/h		
Price	24,819.00 €	28,819.00 €	32,299.00 €

Basic truck

Basic truck	CBH 3.0 (V1: ZT3300, ISS, ZH1)	CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1)	CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)
Part number	52536543	52536545	52536547
Load capacity/load	3000 kg		
total width	1210 mm		
Turning radius	2379 mm		
Throughput	180 t/h		
Load centre distance	500 mm		
Fork dimensions	45 x 122 x 1150 mm		
Tyres	Super-elastic (SE)		
Tyre size, front	28x9-15		
Tyre size, rear	200/50-10		
Fork carriage connection class	3A		
Type of drive control	AC		
Drive motor, performance S2 60 min	17 kW		
Operation	Seat		
Lift motor, performance with S3	26 kW		
Energy consumption according to EN cycle	10.73 kWh/h		
Price	26,109.00 €	30,289.00 €	33,769.00 €

Standard equipment

Name	CBH 2.5 (V1: ZT3300, ISS, ZH1)	CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1)	CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3)
Mast, ZT, h3 = 3300 mm, h1 = 2240 mm, 6 / 10 °	•		
Mast, DZ, h3 = 4800 mm, h1 = 2265 mm, 6 / 6 °		•	•
Auxiliary hydraulics, ZH 1, 1x fixed connection	•		
Auxiliary hydraulics, ZH 2, 2x changeable connection ¹			•
Auxiliary hydraulics, ZH 2, 1x changeable connection, 1x fixed connection ¹		•	
Hydraulic control via mechanical levers	•	•	•
Forks, ISO 2A, 40 x 122 x 1,150 mm	•	•	•
Sideshift, hooked on (ASS)			•
Sideshift, integrated (ISS)	•	•	
Load guard, height from ground 1,025 mm, width 1,040 mm, ISO 2A	•	•	•
Battery, 80 V, Li-ion, 230 Ah, 18,400 Wh	•	•	•
Earthing strip, antistatic	•	•	•
Floorspot, back		•	•
1 working light, rear (LED)			•
2 working lights, front (LED)	•	•	•
Strobe light (LED)	•	•	•
Combi light, rear (LED)	•	•	•
USB port, 2x Type A	•	•	•
Acoustic warning buzzer when reversing	•	•	•
Standard seat	•	•	
Comfort seat including armrest, right and left			•
Seat belt lock control	•	•	•
Overhead guard (without windows and doors)	•		
Electric heater – 0.8-kW output			•
Rear-view mirror, inside	•	•	•
Handle on B-pillar with horn button	•	•	•
Operator's cabin, Economy 1 (ECO 1) Description: Windscreen made of tempered glass, with windscreen wipers and washer system. Roof window made of tempered glass.		•	
Operator's cabin, Comfort 3 (Com 3) Description: Windscreen made of tempered glass, with windscreen wipers and washer system. Roof window made of tempered glass. Heated rear window made of tempered glass, with windscreen wipers and washer system. 2 steel doors with sliding windows.			•
Trailer coupling	•	•	•
LED display 6.4"	•	•	•
1 - Safety instructions for attachments with clamping function (e.g. bale clamp, barrel clamp, gripper, etc.): Attachments with clamping functions may only be connected to industrial trucks that have a button for enabling additional hydraulic functions. This is not included in the standard scope of delivery. An optional retrofitting package is available from your AntOn distribution partner.			

Standard equipment

Name	CBH 3.0 (V1: ZT3300, ISS, ZH1)	CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1)	CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)
Mast, ZT, h3 = 3300 mm, h1 = 2215 mm, 6 / 10 °	•		
Mast, DZ, h3 = 4800 mm, h1 = 2265 mm, 6 / 6 °		•	•
Auxiliary hydraulics, ZH 1, 1x fixed connection	•		
Auxiliary hydraulics, ZH 2, 2x changeable connection ¹			•
Auxiliary hydraulics, ZH 2, 1x changeable connection, 1x fixed connection ¹		•	
Hydraulic control via mechanical levers	•	•	•
Forks, ISO 3A, 45 x 122 x 1,150 mm	•	•	•
Sideshift, hooked on (ASS)			•
Sideshift, integrated (ISS)	•	•	
Load guard, height from ground 1,095 mm, width 1,100 mm, ISO 3A	•	•	•
Battery, 80 V, Li-ion, 230 Ah, 18,400 Wh	•	•	•
Earthing strip, antistatic	•	•	•
Floorspot, back		•	•
1 working light, rear (LED)			•
2 working lights, front (LED)	•	•	•
Strobe light (LED)	•	•	•
Combi light, rear (LED)	•	•	•
USB port, 2x Type A	•	•	•
Acoustic warning buzzer when reversing	•	•	•
Standard seat	•	•	
Comfort seat including armrest, right and left			•
Seat belt lock control	•	•	•
Overhead guard (without windows and doors)	•		
Electric heater – 0.8-kW output			•
Rear-view mirror, inside	•	•	•
Handle on B-pillar with horn button	•	•	•
Operator's cabin, Economy 1 (ECO 1) Description: Windscreen made of tempered glass, with windscreen wipers and washer system. Roof window made of tempered glass.		•	
Operator's cabin, Comfort 3 (Com 3) Description: Windscreen made of tempered glass, with windscreen wipers and washer system. Roof window made of tempered glass. Heated rear window made of tempered glass, with windscreen wipers and washer system. 2 steel doors with sliding windows.			•
Trailer coupling	•	•	•
LED display 6.4"	•	•	•
1 - Safety instructions for attachments with clamping function (e.g. bale clamp, barrel clamp, gripper, etc.): Attachments with clamping functions may only be connected to industrial trucks that have a button for enabling additional hydraulic functions. This is not included in the standard scope of delivery. An optional retrofitting package is available from your AntOn distribution partner.			

Masts

CBH 2.5 (V1: ZT3300, ISS, ZH1)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage	Part number	Price
Duplex mast ZT	3300 mm	2240 mm	195 mm	4360 mm	6 / 10 °	JH_FG00244	0.00 €
CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage	Part number	Price
Triplex mast DZ	4800 mm	2265 mm	1240 mm	5895 mm	6 / 6 °	JH_FG00245	0.00 €
CBH 3.0 (V1: ZT3300, ISS, ZH1)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage	Part number	Price
Duplex mast ZT	3300 mm	2215 mm	135 mm	4430 mm	6 / 10 °	JH_FG00215	0.00 €
CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage	Part number	Price
Triplex mast DZ	4800 mm	2265 mm	1170 mm	5975 mm	6 / 6 °	JH_FG00216	0.00 €

Options

Drive » Charger	Part number	Price
Charger, external, D400, 80V, 100A, CEE red 32A, 4-pin – 3P+E	52540237	1,689.00 €
available only for: CBH 2.5 (V1: ZT3300, ISS, ZH1), CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3), CBH 3.0 (V1: ZT3300, ISS, ZH1), CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)		
Charger, external, D400, 80V, 100A, CEE red 32A, 5-pin – 3P+N+E	52539398	1,689.00 €
available only for: CBH 2.5 (V1: ZT3300, ISS, ZH1), CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3), CBH 3.0 (V1: ZT3300, ISS, ZH1), CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)		
Charger, external, D400, 80V, 60A, CEE red 32A, 5-pin – 3P+N+E	52540240	869.00 €
[No translation available for:]		
available only for: CBH 2.5 (V1: ZT3300, ISS, ZH1), CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3), CBH 3.0 (V1: ZT3300, ISS, ZH1), CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)		
Charger, external, D400, 80V, 60A, CEE red 32A, 4-pin – 3P+E	52540242	869.00 €
available only for: CBH 2.5 (V1: ZT3300, ISS, ZH1), CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3), CBH 3.0 (V1: ZT3300, ISS, ZH1), CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)		

Appendix

CBH 2.5				Load capacity up to h3 [kg]		
Tyres: SE						
Load pick up devices	Mast type	Tilt [°]	h3 [mm]	c = 500 mm	c = 600 mm	c = 700 mm
Fork carrier (without sideshift)	ZT	6/10	3300	2500	2265	2045
	DZ	6/6	4800	2300	2070	1900
Sideshift integrated or hooked on	ZT	6/10	3300	2400	2165	1945
	DZ	6/6	4800	2200	1970	1800

CBH 3.0				Load capacity up to h3 [kg]		
Tyres: SE						
Load pick up devices	Mast type	Tilt [°]	h3 [mm]	c = 500 mm	c = 600 mm	c = 700 mm
Fork carrier (without sideshift)	ZT	6/10	3300	3000	2720	2480
	DZ	6/6	4800	2600	2360	2160
Sideshift integrated or hooked on	ZT	6/10	3300	2900	2620	2380
	DZ	6/6	4800	2500	2260	2060